

Telephone Nos.: Fax No.: Date Received:

Specs from EFMD/NCR North Div LBAC

## Republic of the Philippines SOCIAL SECURITY SYSTEM NCR OPERATIONS – WEST DIVISION

232 G/F Padilla Delos Reyes Bldg. Juan Luna St. Binondo, Manila Tel. 8395-9897 FAX 243-2464

## **CANVASS FORM**

2021-WEST-MAY-03 Tuesday, May 25, 2021

|                     |  |  | PHILGEPS RE<br>DATE POSTED<br>POSTED BY: |                                |
|---------------------|--|--|--|--------------------------------|
| Sir / Ma            | dam:   |  |  |                                |
| Plea                | ase furnish us with  | your qutation on or before:  | at 4:00 pm. for the f                    | following items:               |
| NO.                 | QUANTITY   | PARTICULARS  | UNIT COST                                | TOTAL COST                     |
|                     | 1,221 pcs.   | PURCHASE AND DELIVERY OF LIGHTS  | P  | P                              |
|                     | CAL SPECIFICATI  | ON:  | STATEMENT                                | OF COMPLIANCE                  |
| plea                | ase see att.   | •  |  |                                |
|                     | D TOTAL APPR   | Year Waranty OVED BUDGET (ABC): P 207,580.88   |  |                                |
| with ap             | oroval of VP Luzy  | ranches (Binondo, Legarda, Manila, Pasay Roxas, Pasay Taft, Rect<br>iminda J. Limcauco of NCR West Division  | o, Reina Regente, <i>Sta l</i>           | Mesa, Tondo and Welcome        |
|                     | Payment Terms:<br>Delivery Terms:<br>Price Validity:                             | Supplier shall be paid in acordance to Government Terms.  15 Calendar Days upon receipt of approved Purchase Order/Job O. Three (3) Months   | der.                                     |                                |
| Note/sa             |  | 1  |  |                                |
|                     | from receipt of No<br>30% Surety Bond<br>The SSS shall wit<br>Please specify the | an ABC of P 100,000.00 and above the winning bidder is required to postice to Proceed/Job Order/Purchase Order equivalent to 5% Cash, Casi callable upon demand of the contract price.  hold the applicable taxes from the amount payable in accordance with B e brand name / model offered. | nier's/Manager's Check,                  | Bank Guarantée/Draft or        |
|                     | OVP NCR West I<br>Quotations not us  | f details, please coordinate with Ellen Grace P. Martinez & Nathalie G<br>Division at telephone no. 395-9897.<br>ing the prescribed/standard canvass form and/or unsealed shall automa<br>ct SSS Number and TIN-(BIR) of supplier/contractor in the quotation for                            | tically be disqualified.                 | ards Committee Start of        |
| 7.)                 |  | offer one (1) quotation only, alternative bids shall be rejected.  |  |                                |
| 8.)                 | Please send you including the follow   | r <u>SEALED QUOTATION/CANVASS/BID</u> to 232 G/F Padilla Delos R wing Eligibility Requirements:  | eyes Building, Juan Lur                  | na St., Binondo, Manila,       |
|                     | a.) Registration CDA (Cooper   | Certificate from SEC (Security Exchange Commission), DTI (Departmen rative Development Authority) for cooperatives, or any proof of such regis   | t of Trade & Industry) for tration.      | or sole proprietorship, or     |
|                     | c.) BIR 2303   | nit issued by the city or municipality where the place of business of the process Research   | ospective bidder is locat                | ed.                            |
|                     | d.) Latest Form  | SSS R-5 Contributions Payment  |  |                                |
| This is to          | certify that my Co   | ompany is updated in the payment of <b>contributions</b> and <b>loans</b> to SSS are   | d the data / quotation ind               | licated are valid.             |
|                     |  | Owner/Company Representative (Sign over Printed Name)  |  |                                |
| REMINE<br>himself t | DER: Price quotation TE  | on should be made with extra care taking into account the specification cRMS & CONDITIONS.   | and unit of quantity to av               | void errors. The offeror binds |
|                     | indicate below y   | our Business Name, Address and Telephone Number  | Very truly y                             | vours,                         |
|                     | usiness Name:<br>usiness Address   |  | LORENZA F. P                             | ANCHO C-NCR West Division      |
|                     | usiness SSS No   |  | Chairman, LDA                            | C. 1. 1                        |
|                     | usiness TIN No.:   |  | by: ELLEN GRACE                          | MV<br>EP MARTINEZ              |
|                     | andbank Accoun   |  | Secretariat                              | - F. MARTINEZ                  |
|                     | Address:   |  | 223/Giariat )                            |                                |

| LED Bulb, 9W, Daylight   Specifications:   Luminous Efficiency: 120-130 LMW:   Luminous Efficience: 130-130 LMW:   Luminous Efficience:  | ltem          | Description  | Amount per piece | Total No. of<br>Request | Total<br>Approved<br>Budget | Bid Amount<br>per piece | Total Bid<br>Amount |
|--|---------------|--|------------------|-------------------------|-----------------------------|-------------------------|---------------------|
| Beam Angle: 150 Degree ; Power. 18W ; Power Supply: Bull-in  | 1             | Specifications: Luminous Efficiency: 120-130 LM/W; Luminous Flux: 2160-2340 Lm Color Temperature: 6500K Daylight; CRI:   | ₱144.84          | 291                     | ₱42,148.44                  |                         |                     |
| Cap Base: G13: Lamp Size: 1200mm Length x 28mm Diametor - Material: Aluminum Heat Sink and PC Frosted Cover - Average Lifetime: 50,000 hours(min) - Standards: CE, RoHS, UL, ETL, TUV, LM79, 18090001  Ta LED Tube Light 16W 4PT Industrial Daylight Specifications: Wattage: 16W   Luminous Flux: 1,600 lm   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: 50,000 hours   Writing: 13 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Ts Tube Light 14W 2FT Industrial Daylight   Specifications: Wattage: 14W   Luminous Flux: 1,400 lm   Dimension: 600 mm   Color Temperature 5000-6500 K / Daylight   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Writing: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Ts Tube Light 12W 4FT Industrial Daylight   Specifications: Wattage: 28W   Luminous Flux: 2,100 lm   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: Flux: 2,100 lm   Dimension: 1,200 mm   Color Temperature: 50,000 hours   Writing: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Electronic Ballast   Specifications:   P44,625,75   P46,667   P1,986,67   P49,667   P1,986,67   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: 150,000 hours   Writing: 15 Connector   Input Voltage: AC 85V - 255V 50/60 Hz   Electronic Ballast   Specifications:   P46,67   P1,986,67   P49,667   P49,667  |               | Beam Angle: 150 Degree ; Power: 18W ;<br>Power Supply: Built-in<br>Voltage: 100-277V ; Line Frequency: 50-60Hz<br>Wiring Connection: Single Ended; General   |                  |                         |                             |                         |                     |
| ### T8 LED Tube Light 16W 4FT Industrial Daylight   Specifications:   Wattage: 150W  |               | Cap Base: G13 ; Lamp Size: 1200mm Length<br>x 26mm Diameter<br>- Material: Aluminum Heat Sink and PC<br>Frosted Cover  |                  |                         |                             |                         |                     |
| Specifications:   Wattage: 16W   Luminous Flux: 1,600 Im   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 18 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   T5 Tube Light 14W 2FT Industrial Daylight   Specifications:   Wattage: 14W   Luminous Flux: 1,400 Im   Dimension: 600 mm   Color Temperature 5500-6500 K / Daylight   Specifications:   Wattage: 14W   Luminous Flux: 1,400 Im   Dimension: 600 mm   Color Temperature 5500-6500 K / Daylight   Specifications:   Wattage: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   T5 Tube Light 28W 4FT Industrial Daylight   Specifications:   Wattage: 28W   Luminous Flux: 2,100 Im   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material: Aluminum Housing + PC Cover   PC Cover: Frosted / Clear   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: > 50,000 hours   Wiring: 15 Connector   Input Voltage: AC 85V - 265V 50/60 Hz   Light Source: High Brightness LED SMD   Beam Angle: 120 Degrees   Lifetime: Sepecifications:   P4,600.00   P4,600.00  |               | LM79, ISO90001   |                  |                         |                             |                         |                     |
| Luminous Flux : 1,600 lm   |               | Specifications:  |                  | 306                     | ₱79,964.69                  |                         |                     |
| Light Source : High Brightness LED SMD   | 2             | Luminous Flux : 1,600 lm  Dimension: 1,200 mm  Color Temperature 6000-6500 K / Daylight  Material : Aluminum Housing + PC Cover  | ₱261.32          |                         |                             |                         |                     |
| TS Tube Light 14W 2FT Industrial Daylight   Specifications:   Wattage : 14W   Luminous Flux : 1,400 lm   Dimension : 600 mm   Color Temperature 5500-6500 K / Daylight   Material : Aluminum Housing + PC Cover   PC Cover : Frosted / Clear   Light Source : High Brightness LED SMD   Beam Angle : 120 Degrees   Lifetime : > 50,000 hours   Wiring : TS Connector   Input Voltage : AC 85V - 265V 50/60 Hz   TS Tube Light 28W 4FT Industrial Daylight   Specifications:   Wattage : 28W   Luminous Flux : 2,100 lm   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material : Aluminum Housing + PC Cover   PC Cover : Frosted / Clear   Light Source : High Brightness LED SMD   Beam Angle : 120 Degrees   Lifetime : > 50,000 hours   Wiring : TS Connector   Input Voltage : AC 85V - 265V 50/60 Hz   Electronic Ballast   Specifications:   Wattage : 28W   Model : Lamp 2 x TS 28W   Electronic Ballast   Specifications:   Wattage : 28W   Electronic Ballast   Specifications:   Wattage : 28W   Electronic Ballast   Specifications:   Wattage : 36W   P14,600.00   Wattage : 36W   P14,000.00   P2,550.00   |               | Light Source : High Brightness LED SMD  Beam Angle : 120 Degrees  * Lifetime : > 50,000 hours  Wiring : T8 Connector   |                  |                         |                             |                         |                     |
| Beam Angle : 120 Degrees   Lifetime : > 50,000 hours   Wiring : T5 Connector   Input Voltage : AC 85V - 265V 50/60 Hz  |               | T5 Tube Light 14W 2FT Industrial Daylight  Specifications:  Wattage: 14W  Luminous Flux: 1,400 lm  Dimension: 600 mm  Color Temperature 5500-6500 K / Daylight  Material: Aluminum Housing + PC Cover  PC Cover: Frosted / Clear | ₱132.83          | 106                     | ₱14,080.33                  |                         |                     |
| Specifications:   Wattage : 28W   Luminous Flux : 2,100 lm   Dimension: 1,200 mm   Color Temperature 6000-6500 K / Daylight   Material : Aluminum Housing + PC Cover   PC Gover : Frosted / Clear   Light Source : High Brightness LED SMD   Beam Angle : 120 Degrees   Lifetime : > 50,000 hours   Wiring : TS Connector   Input Voltage : AC 85V - 265V 50/60 Hz   Electronic Ballast   Specifications:   Wattage : 28W   Model : Lamp 2 x T5 28W   Electronic Ballast   Specifications:   P365.00   40 P14,600.00   Wattage : 36W   P17.00   150 P2,550.00   P2,550.00   P2,550.00   P2,550.00   P2,550.00   P365.00   P3665.00   P3 |               | Beam Angle : 120 Degrees<br>Lifetime : > 50,000 hours<br>Wiring : T5 Connector<br>Input Voltage : AC 85V - 265V 50/60 Hz   |                  |                         |                             |                         |                     |
| Beam Angle: 120 Degrees         Lifetime: > 50,000 hours         Wiring: T5 Connector         Input Voltage: AC 85V - 265V 50/60 Hz         Electronic Ballast         Specifications:         Wattage: 28W         Model: Lamp 2 x T5 28W         Electronic Ballast         Specifications:         Wattage: 36W         P365.00         40         P14,600.00         Wattage: 36W         P17.00         P2,550.00   | 4             | Specifications:  Wattage: 28W  Luminous Flux: 2,100 lm  Dimension: 1,200 mm  Color Temperature 6000-6500 K / Daylight  Material: Aluminum Housing + PC Cover  PC Gover: Frosted / Clear  | ₱149.25          | 299                     | ₱44,625.75                  |                         |                     |
| 5       Specifications:       \$\psi_496.67\$       \$4       \$\psi_1,986.67\$         Wattage : 28W       \$\mathrm{Model : Lamp 2 x T5 28W}\$       \$\mathrm{Electronic Ballast}\$         6       Specifications:       \$\psi_365.00\$       \$40       \$\psi_14,600.00\$         Wattage : 36W       \$\psi_17.00\$       \$150       \$\psi_2,550.00\$  |               | Beam Angle : 120 Degrees<br>Lifetime : > 50,000 hours<br>Wiring : T5 Connector<br>Input Voltage : AC 85V - 265V 50/60 Hz   |                  | ar a                    |                             |                         |                     |
| 6 Specifications: ₱365.00 40 ₱14,600.00 Wattage: 36W ₱17.00 150 ₱2,550.00  | 5             | Specifications:<br>Wattage : 28W   | ₱496.67          | 4                       | ₱1,986.67                   |                         |                     |
| 12/100   | 6             | Electronic Ballast<br>Specifications:  | ₱365.00          | 40                      | ₱14,600.00                  |                         |                     |
| 8   T8 Tube & Box Type Set (18W) #205 00   25   \$7 525 00   | $\overline{}$ |  |                  |                         |                             |                         |                     |
| TOTAL \$\partial partial     |               | T8 Tube & Box Type Set (18W)   | ₱305.00          | 25                      |                             |                         |                     |